

UL TEST REPORT AND PROCEDURE

Standard:	UL 60950-1, 2nd Edition, 2007-03-27 (Information Technology Equipment - Safety - Part 1: General Requirements) CSA C22.2 No. 60950-1-07, 2nd Edition, 2007-03 (Information Technology Equipment - Safety - Part 1: General Requirements)
Certification Type:	Component Recognition
CCN:	QQGQ2, QQGQ8 (Power Supplies for Information Technology Equipment Including Electrical Business Equipment)
Product:	Power Supply
Model:	HWS1000-3, HWS1000-5, HWS1000-6, HWS1000-7, HWS1000-12, HWS1000-15, HWS1000-24, HWS1000-36, HWS1000-48 and HWS1000-60. May be followed by suffix "/CO" or "/HD" (for all models except for Model HWS1000-24), suffix "/CO", "/HD", "/RY", "/RYCO", or "/RYHD" (for Model HWS1000-24 only).
Rating:	Input :100-240VAC, 50/60Hz 9.6A: HWS1000-3 13.5 A: HWS1000-5, HWS1000-6, HWS1000-7, HWS1000-12, HWS1000-15, HWS1000-24, HWS1000-36, HWS1000-48, HWS1000-60 Output: HWS1000-3 :3.3 V, 200 A (maximum 660 W) HWS1000-5 :5 V, 200 A (maximum 1000 W) HWS1000-6 :6 V, 167 A (maximum 1002 W) HWS1000-7 :7.5 V, 134 A (maximum 1005 W) HWS1000-12 :12 V, 88 A (maximum 1056 W) HWS1000-15 :15 V, 70 A (maximum 1050 W) HWS1000-24 :24 V, 46 A (maximum 1104 W) HWS1000-36 :36 V, 30.7 A (maximum 1104 W) HWS1000-48 :48 V, 23 A (maximum 1104 W) HWS1000-60 : 60 V, 18.4 A (maximum 1104 W)
Applicant Name and Address:	TDK-LAMBDA CORP NAGAOKA TECHNICAL CENTER R&D DIV 2704-1 SETTAYA-MACHI NAGAOKA-SHI NIIGATA 940-1195 JAPAN

Issue Date: 2010-06-03
2012-05-17

Page 2 of 22

Report Reference #

E122103-A58-UL

This is to certify that representative samples of the products covered by this Test Report have been investigated in accordance with the above referenced Standards. The products have been found to comply with the requirements covering the category and the products are judged to be eligible for Follow-Up Service under the indicated Test Procedure. The manufacturer is authorized to use the UL Mark on such products which comply with this Test Report and any other applicable requirements of UL LLC ('UL') in accordance with the Follow-Up Service Agreement. Only those products which properly bear the UL Mark are considered as being covered by UL's Follow-Up Service under the indicated Test Procedure.

The applicant is authorized to reproduce the referenced Test Report provided it is reproduced in its entirety.

UL authorizes the applicant to reproduce the latest pages of the referenced Test Report consisting of the first page of the Specific Technical Criteria through to the end of the Conditions of Acceptability.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL.

Prepared by: Hiroyuki Furuya

Reviewed by: David Keen

Supporting Documentation

The following documents located at the beginning of this Procedure supplement the requirements of this Test Report:

- A. Authorization - The Authorization page may include additional Factory Identification Code markings.
- B. Generic Inspection Instructions -
 - i. Part AC details important information which may be applicable to products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of this Test Report.
 - ii. Part AE details any requirements which may be applicable to all products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of each Test Report.
 - iii. Part AF details the requirements for the UL Certification Mark which is not controlled by the technical standard used to investigate these products. Products are permitted to bear only the Certification Mark(s) corresponding to the countries for which it is certified, as indicated in each Test Report.

Product Description

These units are component type AC/DC Switching Power Supply equipping FAN Motor intended for use in the Information Technology Equipment. These units are not temperature dependent equipments.

Model Differences

1. All models are identical, except for Output Rating, Transformer (T201), Inductor (L401), Thermostat (TH201) and some components on secondary circuit.
2. Suffix /CO type: Model with conformal coating on solder side of PWB.
3. Suffix /HD type: Model with conformal coating on solder and component side of PWB.
4. Suffix /RY type (for Model HWS1000-24 only): Model with relay signal outputs (R-NO and R-NC) as Power Fail signal.
5. Suffix /RYCO type (for Model HWS1000-24 only): Suffix /RY type with conformal coating on solder side of PWB.
6. Suffix /RYHD type (for Model HWS1000-24 only): Suffix /RY type with conformal coating on solder and component side of PWB.

Technical Considerations

- Equipment mobility : for building-in
- Connection to the mains : N/A
- Operating condition : continuous
- Access location : operator accessible
- Over voltage category (OVC) : OVC II
- Mains supply tolerance (%) or absolute mains supply values : +10%, -15%
- Tested for IT power systems : No
- IT testing, phase-phase voltage (V) : NA
- Class of equipment : Class I (earthed)

- Considered current rating (A) : 20
- Pollution degree (PD) : PD 2
- IP protection class : IP X0
- Altitude of operation (m) : Up to 2000
- Altitude of test laboratory (m) : Approximately 10 to 20
- Mass of equipment (kg) : Approx 3.0
- The product was submitted and evaluated for use at the maximum ambient temperature (T_{ma}) permitted by the manufacturer's specification of: (At Input Voltage over 90Vac) Models except HWS1000-5: 50°C [for using 100% load of output rating] and 71°C [for using 50% load of output rating], Model HWS1000-5: 40°C [for using 100% load of output rating] and 71°C [for using 50% load of output rating] .(At Input Voltage over 85Vac) Models except HWS1000-5: 50°C [for using 80% load of output rating] and 71°C [for using 40% load of output rating], Model HWS1000-5: 40°C [for using 80% load of output rating] and 71°C [for using 40% load of output rating] .
- The product is intended for use on the following power systems: IT, , TN

Engineering Conditions of Acceptability

For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC. When installed in an end-product, consideration must be given to the following:

- The end-product Electric Strength Test is to be based upon a maximum working voltage of: Primary-SELV: 253 Vrms, 600 Vpk
- The following secondary output circuits are SELV: Output circuit of Models HWS1000-3, HWS1000-5, HWS1000-6, HWS1000-7, HWS1000-12, , HWS1000-15, HWS1000-24, , HWS1000-36 and HWS1000-48.
- The following secondary output circuits are at hazardous energy levels: Output circuit of All models.
- The power supply terminals and/or connectors are: Suitable for factory wiring only ,
- The maximum investigated branch circuit rating is: 20 A
- The investigated Pollution Degree is: 2
- Proper bonding to the end-product main protective earthing termination is: Required
- The following input terminals/connectors must be connected to the end-product supply neutral: The terminal marked "AC (N)" in terminal block (TB1)
- The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation

system with the indicated rating greater than Class A (105°C): T201 (Class F), T202 and T203 (Class B), T700 (Class B) ,

- The following end-product enclosures are required: Fire, Mechanical
- Cover and Chassis have not been evaluated as externally/internal enclosure.
- The unit is equipping the Variable Resistor (VR900) used for output voltage adjustment of rated output. See Additional Information.
- The pattern trace connected to "FG" Terminal of Terminal Block (TB1) has not performed Limited Short-Circuit Test in CSA C22.2 No. 04. Also, these "FG" Terminal/ pattern trace were isolated from primary circuit by basic insulation only. The chassis of this component must be properly connected to the Protective Earthing Conductor or Protective Earthing Terminal in the end-product via Protective Bonding Conductor.
- All tests measuring temperatures of components were performed with the unit mounted to horizontal position (Nameplate/Rating Label side up).

Additional Information

Adjustable output range by the Variable Resistor (VR900) and remote sensing are as follow.

- HWS1000-3: 2.64 to 3.96 Vdc, Maximum 200 A, Maximum 660 W.
- HWS1000-5: 4.0 to 6.0 Vdc, Maximum 200 A, Maximum 1000 W.
- HWS1000-6: 4.8 to 7.2 Vdc, Maximum 167 A, Maximum 1002 W.
- HWS1000-7: 6.0 to 9.0 Vdc, Maximum 134A, Maximum 1005 W.
- HWS1000-12: 9.6 to 14.4 Vdc, Maximum 88A, Maximum 1056 W.
- HWS1000-15: 12.0 to 18.0 Vdc, Maximum 70A, Maximum 1050 W.
- HWS1000-24: 19.2 to 28.8 Vdc, Maximum 46A, Maximum 1104 W.
- HWS1000-36: 28.8 to 43.2 Vdc, Maximum 30.7A, Maximum 1104 W.
- HWS1000-48: 39.4 to 52.8 Vdc, Maximum 23 A, Maximum 1104W.
- HWS1000-60: 48 to 66.0 Vdc, Maximum 18. 4A, Maximum 1104W.

Note: Each output wattage can be used when Input voltage is over 90 Vac and Tma is 50°C except Model HWS1000-5 (Tma is 40°C). See CE1.2 in Engineering Consideration, when Tma is exceeding these temperature.

The additional evaluation item according to the standard upgrade was included in the Clause List.

Markings and instructions

Clause Title	Marking or Instruction Details
1.7.1 Power rating - Model	Model Number
1.7.1 Power rating - Company identification	Listee's or Recognized company's name, Trade Name, Trademark or File Number
1.7.6 Fuses - Rating	Rated current and voltage and type located on or adjacent to fuse or fuseholder.

Special Instructions to UL Representative

Inspect the transformer(s) listed in BD1.1 per AA1.1-C. When the tests are conducted at other location, inspect test record and specification sheet provided by the component manufacturer. Verify the specification sheet indicates 100% routine test specified in BD1.1 be conducted at the Component manufacturer.